



# STYN1865

## Discrete Thyristors(SCRS)




A(TAB)

K=Cathode, A=Anode, G=Cate



### Dimensions TO-247AD

Industry standard outline  
RoHS compliant  
Epoxy meets UL 94V-0



Dim.	Millimeter		Inches	
	Min.	Max.	Min.	Max.
A	19.81	20.32	0.780	0.800
B	20.80	21.46	0.819	0.845
C	15.75	16.26	0.620	0.640
∅D	3.15	3.65	0.124	0.144
E	4.32	5.49	0.170	0.216
F	5.40	6.30	0.213	0.248
G	1.65	2.18	0.065	0.086
H	3.80	4.50	0.150	0.177
J	1.00	1.40	0.039	0.055
K	10.80	11.10	0.425	0.437
L	4.70	5.30	0.185	0.209
M	0.40	0.80	0.016	0.031
N	1.50	2.49	0.059	0.098

	V <sub>RRM</sub> V	V <sub>RSM</sub> V
<b>STYN1865</b>	1800	1900

Symbol	Test Conditions	Maximum Ratings	Unit
I <sub>TRMS</sub> I <sub>TAVM</sub>	T <sub>VJ</sub> =T <sub>VJM</sub> T <sub>C</sub> =75°C; 180° sine	65 41	A
I <sub>TSM</sub>	T <sub>VJ</sub> =45°C V <sub>R</sub> =0 t=10ms (50Hz), sine t=8.3ms (60Hz), sine	520 560	A
	T <sub>VJ</sub> =T <sub>VJM</sub> V <sub>R</sub> =0 t=10ms(50Hz), sine t=8.3ms(60Hz), sine	460 500	
i <sup>2</sup> <sub>t</sub>	T <sub>VJ</sub> =45°C V <sub>R</sub> =0 t=10ms (50Hz), sine t=8.3ms (60Hz), sine	1350 1300	A <sup>2</sup> s
	T <sub>VJ</sub> =T <sub>VJM</sub> V <sub>R</sub> =0 t=10ms(50Hz), sine t=8.3ms(60Hz), sine	1050 1030	
(di/dt) <sub>cr</sub>	T <sub>VJ</sub> =T <sub>VJM</sub> f=50Hz, t <sub>p</sub> =200us V <sub>D</sub> =2/3V <sub>DRM</sub> I <sub>G</sub> =0.3A dig/dt=0.3A/us repetitive, I <sub>T</sub> =40A	150	A/us
	V <sub>D</sub> =2/3V <sub>DRM</sub> I <sub>G</sub> =0.3A dig/dt=0.3A/us non repetitive, I <sub>T</sub> =I <sub>TAVM</sub>	500	
(dv/dt) <sub>cr</sub>	T <sub>VJ</sub> =T <sub>VJM</sub> ; R <sub>GK</sub> =∞; method 1 (linear voltage rise) V <sub>DR</sub> =2/3V <sub>DRM</sub>	1000	V/us
P <sub>GM</sub>	T <sub>VJ</sub> =T <sub>VJM</sub> I <sub>T</sub> =I <sub>TAVM</sub> t <sub>p</sub> =30us t <sub>p</sub> =300us	10 5	W
		0.5	
P <sub>GAV</sub>		0.5	W
V <sub>RGM</sub>		10	V
T <sub>VJ</sub> T <sub>VJM</sub> T <sub>stg</sub>		-40...+140 140	°C
		-40...+125	
V <sub>ISOL</sub>	50/60Hz, RMS t=1minute, leads-to-tab	2500	V~
M <sub>d</sub> F <sub>c</sub>	Mounting torque (M3)	0.8...1.2	Nm
	Mounting force with clip	20...120	N
Weight		6	g

**Sirectifier**<sup>®</sup>

# STYN1865

## Discrete Thyristors(SCRS)

Symbol	Test Conditions	Characteristic Values	Unit
$I_R, I_D$	$T_{VJ}=T_{VJM}; V_R=V_{RRM}; V_D=V_{DRM}$	5	mA
$V_T$	$I_T=80A; T_{VJ}=25^{\circ}C$	1.64	V
$V_{TO}$	For power-loss calculations only ( $T_{VJ}=125^{\circ}C$ )	0.85	V
$r_T$		11	m $\Omega$
$V_{GT}$	$V_D=6V; T_{VJ}=25^{\circ}C$ $T_{VJ}=-40^{\circ}C$	1.5 1.6	V
$I_{GT}$	$V_D=6V; T_{VJ}=25^{\circ}C$ $T_{VJ}=-40^{\circ}C$	100 200	mA
$V_{GD}$	$T_{VJ}=T_{VJM}; V_D=2/3V_{DRM}$	0.2	V
$I_{GD}$		10	mA
$I_L$	$T_{VJ}=25^{\circ}C; t_p=10\mu s;$ $I_G=0.3A; di_G/dt=0.3A/\mu s$	150	mA
$I_H$	$T_{VJ}=25^{\circ}C; V_D=6V; R_{GK}=\infty$	100	mA
$t_{gd}$	$T_{VJ}=25^{\circ}C; V_D=1/2V_{DRM}$ $I_G=0.3A; di_G/dt=0.3A/\mu s$	2	$\mu s$
$R_{thJC}$	DC current	0.62	K/W
$R_{thJH}$	DC current	0.82	K/W
a	Max. acceleration, 50 Hz	50	m/s <sup>2</sup>




Fig. 1 Gate trigger range




Fig. 2 Gate controlled delay time  $t_{gd}$



# STYN1865

## Discrete Thyristors(SCRS)




Fig.3 Forward characteristics




Fig.4 Surge overload current  
 $I_{TSM}$ : crest value,  $t$ : duration




Fig.5  $I^2t$  versus time (1-10 ms)




Fig.6 Power dissipation versus forward current and ambient temperature





Fig.7 Max. forward current at case temperature

### MARKING



### ORDERING INFORMATION

Part Number	Package	Shipping	Marking Code
STYN1865	TO-247AD	30pcs / Tube	STYN1865

